

*IN THE SPECIFICATION*

The insert previously added to page 3 of the specification should read:

B1  
"This is a strong, flexible strap, cable or chain, attached to the frame at one end and of sufficient length to ~~warp~~ wrap around a part of the fork truck and, at the other end, terminated in a loop, or some equivalent for fastening the truck and frame together."

The insert previously added to page 5 of the specification should read:

B2  
"In yards handling coils of metal, it is common to use ram trucks. These are fork truck with the fork assembly unfastened and replaced by a moldboard **106** onto which a length of heavy pipe has been mounted to act as a "ram" **104**. The operator simply runs this ram **104** into the core of a coil to lift and transport it. Figures 6 and 7 show an alternate embodiment of the rail car lid lifter **10** in which the base **12** is considerably enlarged in height to accommodate a through collar **102**, welded in place under the top member of base **12**. This collar is sized so that a ram **104** is an easy fit inside as seen in Figure 7. Pockets **108** and **110** are provided so that lifter **10** can be used with a regular fork truck as well. The advantage of using the ram-adapted configuration is that the same truck unit can handle lids and coils. For safety, moldboard **106** and lifter **10** have attached matching ears **112** with holes, one on one member and two on the other, that engage aligning the holes so that a pin, not shown, can lock the two units together. Figure 6 also shows an optional accessory which is shackle ~~**112**~~ **114** to which a safety hook or the like can be attached. ~~This arrangement is useful for various lifting operations such as lifting boat engines from boats pulled alongside piers.~~"

On page 4, the paragraph beginning on line <sup>8</sup>/~~8~~ should read"

B3  
"Lifter 10 is shown in Figure 2 with base 12 engaged on forks 36 of the  
fork truck. These have been lifted high enough for boom 16 to be inserted  
into handle ~~102~~ 28 and then lifted so that fitting 30 engages and then lifts  
handle ~~102~~ 28 and lid 26."

On page <sup>5</sup>/~~4~~, the first full sentence beginning on line <sup>2</sup>/~~29~~ should read:

NE B4  
"Fish plates ~~17~~ 21 reinforce the welded joints."

On page 5, the first full sentence beginning on line 4 and ending on line 5 should  
read:

NE B5  
"A further slight lift engages saddle fitting 30 with handle ~~102~~ 28."